

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>ERSE CABLU VBAPV & VBAPV-K 200 X 2 X 0.50, ERSE</u> construc?ie 1. CONDUCTOR IEC 60228, VDE 0295, EN 60228 Clasa 1 Cupru solid ELEKTROLYTIC 2. IZOLARE PVC combinate 3. Cod culoare TS 2814 4. E?uare în straturi de pana la 10 perechi 20 de perechi, 100 perechi = IMPREUNA E?uare a SUB grupuri, cu 10 perechi 5. Placarea cu band? de PES. (Peste 10 perechi) 6. SCREEN cupru cositorit DRAIN WIRE TAPE AL-PES 7. MANTA PVC combinate 8. MANTAUA CULOARE RAL 7032 GREY cei care nu Mici Raza de îndoire -Ignifug CARACTERISTICA NOT?: VBAPV = conductor de cupru ELEKTROLYTIC VBAPV-K = conductor de cupru stanat Caracteristici tehnice 1. CONDUCTOR REZISTEN?A 0,50 mm = 97.8Ω/km 2. Rezisten?a izola?iei 500MΩ.km 3. MUTUAL CAPACITATE 120 nF / km (max) 4. Interval de temperatur? -30 ° C ~ + 80 ° C 5. Tensiunea de încercare 1000 V 6. Tensiune de 250 V 7. Raza de îndoire 8x cablu Ø 8. De testare a flacarii IEC 60332-1-2/VDE 0482 332-1-2 TS EN 60332-1-2 cerere Pentru instala?ii de interior, centrala telefonic? ?i distribu?iile abonat. Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/cablu-vbapv-vbapv-k-200-x-2-x-0-50-erse
--	---