

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



CAVI VENTILATOR TUBULATURA 100MM 300MC/H

Ventilator din plastic pentru tubulatura.
Schema de montaj si domeniul de aplicare se poate vedea in poza secundara.
Material constructiv - PP
Temperatura maxima de lucru +35 grade celsius
Alimentare la 230V/50hz
Grad de protectie IP 44
Culoare verde deschis
Sunet 60 Db
Turatie 2400 rotatii / minut
Putere electrica 70W
Flux de aer evacuat 300 mc / ora

Dimensiuni			
ØA	tubulatura	Inaltime	Diametru total
WK plastics Ø100	99	248	288
WK plastics Ø125	124	248	288
WK plastics Ø150	149	230	379
WK plastics Ø160	159	230	379
WK plastics Ø200	199	258	379
WK plastics Ø250	249	255	379
WK plastics Ø315	315	278	453

--	--	--	--	--	--	--	--

type	unit	WK Plastic	WK Plastic	WK Plastic	WK Plastic
		Ø100	Ø125	Ø150	Ø160
Air flow	m3/h	300	480	520	580
Static pressure	Pa	360	330	330	330
Static pressure	mmH2O	37,72	35,17	35,17	35,17
Acoustic pressure	dB(A)	60	61	62	62
Power supply voltage	V/Hz	230/50	230/50	230/50	230/50
Motor rotation	rpm	2400	2400	2400	2400
Power	W	70	70	70	70
Current consumption	A	0,3	0,3	0,3	0,3
Max. Working Temp.	oC	35	35	35	35
Weight	kg	2,01	2,05	2,4	2,4
IP Code	IP	44	44	44	44
Insulation class					

--	--	--	--	--	--	--

Pret: 322,48 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/ventilator-tubulatura-100mm-300mc-h>