

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>SCHRACK RELEU TERMIC 1.8... 2.5 A SHRACK</u> Releu Termic 1.8 ... 2.5 A Shrack Marimea 0 Funcții: -deconectarea consumatorilor de curent alternativ la suprasarcina de curent . -realizarea sistemelor de comanda a conumatorilor -se foloseste ca un component operativ in tablourile electrice de comanda a motoarelor asincron -coeficient de stabilitate a caracteristiciolr de curent inalt Performante Tehnice: -Tensiune nominala pana la 690V Ac ,50/60hz -Diapazoane functionale pana la 690Vac -Tensiune de izolare >690V -coeficient de siguranta tensiune de impuls 6000v -anduranta electrica -1000000 cicluri -anduranta mecanica -1000000 cicluri -indicatie pentru declansarea protectiei -Material plastic neinflamabil rezistent la UV -Temperatura de lucru -10+60 grade celsius Pret: 50,10 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/releu-termic-1-8-2-5-a-shrack-4359
---	---